

5       **SIMULTANEOUS VISUAL AND TELEPHONIC ACCESS TO INTERACTIVE  
          INFORMATION DELIVERY**

10       FIELD OF THE INVENTION

10               The present invention generally relates to providing access to an  
interactive information delivery system. More particularly, the present invention relates  
to supporting both voice-based and visual-based content delivery by using both  
telephone-based and network-based access points to an interactive information delivery  
system.

15       BACKGROUND OF THE INVENTION

20               One of the challenges facing electronic commerce (e-commerce) is  
overcoming the propensity of Internet consumers to improperly navigate an e-commerce  
website. In fact, many Internet consumers abandon selected products (e.g., products  
placed in a shopping cart) before completing an Internet purchase transaction. Usability  
studies indicate that many abandoned sales transactions directly result from the Internet  
consumer's inability to navigate the e-commerce website.

25               Many e-commerce websites have taken steps to make user navigation  
easier by simplifying the e-commerce website. However, e-commerce retailers market  
their products to consumers having a variety of computer skills. Consequently, many  
efforts to simplify the navigation of a website, may result in frustrating more  
sophisticated consumers. Another approach to simplifying website navigation has been  
to provide an online assistant. Typically, the online assistant is a human operator that

communicates with the e-commerce consumer via a messaging system. Unfortunately, this approach is very expensive, because it requires a staff of operators to support the e-commerce website.

Similar problems exist in the area of automated telephone information systems. Such systems are often referred to as Interactive Voice Response (IVR) systems and are used to provide information and/or call routing by leading a user through a series of menu-driven prompts. For example, IVR systems are commonly used to automate voicemail systems or customer service systems. IVR Systems are commonly used for automating customer service call routing and automated account information (e.g., bank account information). Often, users of IVR systems have problems navigating through the menu tree. Such users often abandon their quest for information and terminate the telephone call, prior to reaching the sought information. When a user abandons an automated information delivery system, the user will typically seek a human attendant to contact to provide the information originally sought. This increases the demand for human operators to support the IVR system. Operators add unnecessary expense to the cost of operating an automated information delivery system.

In addition, because users are required to traverse a menu tree, it is common that users become frustrated with menu-driven information delivery systems and resort to contacting a human operator. Typically menu-driven information delivery systems do not enable the user to jump directly to the desired information and/or service, but require that the user traverse a predefined path through the menu tree to the user's objective.

Therefore, there is a need in the art for an information delivery system that reduces the occurrence of user abandonment. The information delivery system should combine the functionality of a website-based information delivery system and a telephone-based information delivery system. The information delivery system also should provide integrated user interaction, whereby the web-based information delivery system is responsive to commands issued by a user via the telephone-based information delivery system and vice-versa. Finally, the information delivery system should provide

short cuts to enable a user to quickly access information and eliminate repetitive menu traversals.

#### SUMMARY OF THE INVENTION

5           The present invention integrates components of an Advanced Intelligent Network (AIN) with Internet-based resources to provide simultaneous visual and telephonic access to an interactive information delivery system. The present invention enhances conventional Interactive Voice Response (IVR) systems by enabling the simultaneous delivery of visual information that corresponds to the voice-based  
10 information that is delivered telephonically. A user that contacts an IVR service provider (IVR host) by telephone is provided with the option of a Visual IVR (VIVR) session, rather than the conventional voice-only (i.e., telephony-based) IVR session. The user will only be provided the VIVR session option if a determination is made that the user has an existing Internet connection that will support a VIVR session. The VIVR session  
15 provides visual information to the user in the form of visually formatted web pages delivered over an Internet connection and provides audible message information over a conventional voice telephone connection.

          A VIVR session can enable the delivery of visual information and the delivery of telephony-based information such that the user hears an audible message on  
20 the telephone that corresponds to the information displayed on a networking device (e.g., a computer running a conventional web browser). The user may provide instructions to a VIVR Server over either the telephone (e.g., using voice commands or DTMF key code commands) or the networking device (e.g., selecting a hyperlink). The VIVR Server will respond to instructions received by either the telephone connection or the Internet  
25 connection and will modify the delivery of the voice-based and visual-based information, accordingly.

          A VIVR session can be enabled based on the existence of a VIVR Session ID in a Session ID database. The presence of the VIVR Session ID in the Session ID database indicates that the user has an active Internet connection that can support a VIVR

session. The absence of a VIVR Session ID in the Session ID database indicates that the user does not have such an Internet connection. In response to a determination that an applicable VIVR Session ID is present in the Session ID database, the VIVR Server can prompt a user to initiate a VIVR session.

5           The present invention incorporates the functionality of a telephone-based information delivery system with that of a website-based information delivery system. The integrated functionality of the information delivery systems is provided by interconnections between a wireline or wireless telephone system and the Internet. By enabling an Advanced Intelligent Network (AIN) Service Control Point (SCP) to  
10       communicate over the Internet using accepted Internet standards (e.g., TCP/IP), the present invention integrates the functionality of a VIVR application server with a Voice XML (VXML) gateway. The functionality of the visual and voice information is coordinated by use of a Session ID database. The integration of these subsystems permits the simultaneous delivery of visual information via the Internet and voice information via  
15       a telephone connection. The user may issue commands through either the voice-based system or the visual-based system and both systems will respond to the issued commands.

          The various aspects of the present invention may be more clearly understood and appreciated from a review of the following detailed description of the  
20       disclosed embodiments and by reference to the drawings and claims.

#### BRIEF DESCRIPTION OF THE DRAWINGS

          Figure 1 is a block diagram depicting a conventional Advanced Intelligent Network connection between a voice line telephone and an Interactive Voice Response  
25       server.

          Figure 2 depicts a conventional connection between a networking device and a web server.

Figure 3 is a block diagram depicting a Visual Interactive Voice Response automated information delivery system that is an exemplary embodiment of the present invention.

Figure 4 is a flow chart depicting an exemplary method for initiating and terminating a VIVR session.

Figure 5 is a block diagram of an exemplary embodiment of the present invention that employs a Voice XML gateway.

Figure 6 is a block diagram depicting the interaction between an exemplary VIVR Server and an exemplary VXML translation unit.

Figure 7 is a flow chart depicting an exemplary method for providing simultaneous visual and telephonic access to an exemplary VIVR system.

## DETAILED DESCRIPTION

### Exemplary Operating Environments

Fig 1 is a block diagram depicting a conventional Advanced Intelligent Network connection between a voice line telephone **100** and an Interactive Voice Response (IVR) server **102**. Modern telephone switching conforms to a telecommunications protocol referred to as Signaling System 7 (SS7). The Advanced Intelligent Network (AIN) **101** is a telecommunications switching network that utilizes the SS7 protocol to connect switching centers and other telecommunications resources to provide call routing and various other services to telephone users. Essentially, the AIN **101** is a collection of telecommunications components and interconnections that support the generation of AIN messages known as triggers and enable the components to respond to generated triggers by generating responsive messages or by executing an instruction. The voice line telephone **100** is connected to the AIN **101** at a Central Office switch **104**. The Central Office switch **104** is also referred to as Service Switching Point (SSP). The Central Office switch **104** will, hereinafter, be referred to as the SSP **104**. A Central Office Switch **104** may have a plurality of subscriber lines connected thereto. The AIN

can have an indefinite number of SSP's **104, 106**. The SSP's **104** and **106** communicate with each other over an SS7 protocol data communication link **108** and with other AIN telecommunications components over other SS7 data links **110, 112**.

Much of the intelligence utilized by the AIN **101** to switch calls and provide other telecommunications services resides in a Service Control Point (SCP) **114**. As is known to those skilled in the art, SCPs were initially integrated into the AIN **101** to handle message translations and billing transactions for the implementation of 800-number services. An 800 number subscriber has at least one directory number (DN) that can be called by a telephone user. Because there is no physical central office or geographic area that corresponds to the 800 area code, it is more economical to provide a few central locations at which a lookup of the directory number for an 800 call can be made, than to provide the requisite translation information at all SSPs. SCPs may have associated databases for directory numbers corresponding to functional 800 numbers.

SCPs also may have databases that identify customers that are subscribers to one or more telecommunication services (e.g., caller ID). In order to maximize the efficiency of processing data and calls at each SSP **104, 106**, a relatively small set of triggers are defined for each call and/or service. A trigger in the AIN **101** is an event associated with a particular subscriber line that generates a data packet to be sent to an SCP. The trigger is usually generated by an SSP and causes the SCP to query one or more of its associated databases to determine whether some calling feature or service should be implemented for a particular call. The results of this database query are returned to the SSP **104, 106** from the SCP **114** in a return data packet. The return data packet includes instructions to the SSP **104, 106** as to how to process the call. The instructions may be to take some special action as a result of a calling feature or service, or may simply be an indication that there is no entry in the database that indicates that anything other than ordinary telephone switching should be provided for the call. In short, the SCP **114** is a sophisticated, computerized switching system that responds to data packets and/or triggers over the SS7 data links **110, 112** to route calls and to

interconnect telecommunications components and AIN users to provide telecommunications services.

In summary, the AIN is a complex, high-speed, high call volume, packet-switched messaging system that provides a great deal of versatility in the handling of telephone calls. The SSP switch will generate a trigger and then wait for a response from the SCP 114 before proceeding with call processing. More detailed information regarding the AIN 101 can be found in U.S. Patent Number 5,430,719, which is commonly assigned to BellSouth Intellectual Property Management Corporation and is incorporated herein by reference.

In the example depicted in Figure 1, a user of the telephone 100 can contact an IVR application server 102 by dialing a directory number associated with the IVR server. A telecommunication path can be created between the telephone 100 and the IVR server 102 via the AIN 101. The IVR server 102 can be used to provide automated information to the user of the telephone 100. Such information might include stock quotes, bank records, or customer service information. Typically, an IVR server 102 will utilize a menu-driven system that will respond to key punches (known as DTMF key codes) entered on the telephone 100. For example, the IVR server may send a message to the telephone 100 that includes a list of options. The user of the telephone 100 may select an option by entering a number on the keypad of the telephone 100. The IVR server 102 may respond to the entry by providing the user with an audible message the selected information (e.g., a current stock quote) or may provide the user with another list of options that pertain to the user's previously selected option. Thus, a user can access an automated voice-based information delivery system hosted by the IVR server 102, via the AIN 101.

Figure 2 depicts a conventional connection between a networking device 250 and a web server 252. Typically, the networking device 250 can connect to the web server 252 via an SSP 254 connection to an Internet Service Provider (ISP) 258. The Internet appliance 250 can initiate the connection by dialing a directory number of the ISP 258 and initiating a conventional login procedure. The connection between the SSP

254 and the ISP 258 may be over a TCP/IP connection 256 or via an SS7 connection to an SCP 155. The SCP 155 may be connected to the ISP 258 via another TCP/IP connection or via an SS7 connection. The ISP 258 can connect to the web server 252 via an IP Network (e.g., the Internet 260) in the conventional manner. A security firewall 5 262 may protect the web server 252 from unauthorized access over the Internet 260.

Accordingly, the Internet appliance 250 and the conventional telephone 100 can utilize the AIN to gain access to the web server 252. In an exemplary embodiment of the present invention, the connection between the Internet appliance 250 and the web server 252 and the connection between the telephone 100 (Fig. 1) and the 10 IVR application server 102 (Fig. 1) can be coordinated so that a single user of the telephone 100 and of the Internet appliance 250 can simultaneously access the functionality of both the IVR application server and the web server.

#### An Exemplary Visual IVR System

15 An exemplary embodiment of the present invention provides a synchronized, simultaneous telephony-based and visual presentation of IVR applications. This integrated telephony-based and Internet-based presentation of IVR applications is referred to as Visual IVR or VIVR. VIVR provides users with convenient access to automated information delivery systems hosted by a VIVR Server. This results in more 20 efficient and more effective interaction between a user/consumer and the automated information delivery system in the context of a VIVR session. Automated information delivery system providers can augment telephony based information delivery with Internet-based (i.e., visual-based) information delivery to enhance the provider's automated information delivery system. Similarly, web site operators can augment a web 25 site with telephony-based (i.e., voice based) information delivery to enhance the ability of users to navigate the web site by, for example, providing a voice-based help system.

A typical VIVR session may be enabled when the user connects to the user's ISP. Upon connection, the user may navigate to the website of a VIVR provider (VIVR Server host). The website may inform the user that simultaneous audio and visual

09394206 DEB01



information can be provided to assist the user. Then, the user may use a conventional telephone to establish a telephony-based connection to the VIVR host. In one embodiment of the present invention, the telephony network may be used to play an announcement inviting the user to initiate a VIVR session.

5 If the user selects to enable VIVR, then the automated information will be presented to the user simultaneously, visually and audibly. That is, the user will be presented with the information on the user's networking device as well as on the user's telephone. Notably, the user may disable the telephony-based access, the visual-based access, or both access points at any time.

10 Figure 3 is a block diagram depicting a Visual IVR (VIVR) automated information delivery system that is an exemplary embodiment of the present invention. The system depicted in Figure 3 uses a VIVR Server 352 to provide automated information delivery to a user of a telephone 300. This system also can be used to provide automated information delivery to a personal computer, Internet appliance, or  
15 T.V. browser (collectively, networking device 350), via a network connection (e.g., an Internet connection). The telephone 300 and the networking device 350 may be connected to an SSP 354 over separate telephone lines or over a single telephone line utilizing a conventional Asymmetric Digital Subscriber Line (ADSL) modem 374. Those skilled in the art will appreciate that any connection to the AIN would enable the  
20 implementation of exemplary embodiments of the present invention.

VIVR refers to the integration of voice-based and Internet-based automated information delivery systems. By using a networking device 350, a user can initiate a VIVR session by connecting to the VIVR Server 352 via the Internet 360. In the embodiment of the present invention depicted in Figure 3, the VIVR Server 352 is  
25 accessed through a secure intranet 372 that is protected from unauthorized users by a firewall 362.

A VIVR session may begin when a telephone call to an ISP is initiated by the networking device 350 and initially processed by the SSP 354 associated with the ISP. As part of a dial-up procedure, the networking device 350 may send an AIN feature

code trigger to the SSP that will, in turn, cause the SSP to generate a trigger, such as the well-known TCAP INFO ANALYZED QUERY to the SCP 355, via SS7 data link 310. The feature code trigger also can be generated as part of a preconfigured login procedure. The SCP 355 can then instruct the SSP 354 to route the call to the ISP 358. The SCP 355  
 5 may also instruct the SSP 354 to notify the SCP 355 when the call is terminated by the networking device 350. The SSP 354 will then route the call to the ISP 358.

The SSP 354 will receive a data packet from the networking device 350. The data packet may include the Internet directory number (DN), the Internet protocol (IP) address of the networking device 350, and the voice DN. A directory number is  
 10 simply the telephone number assigned to the telephone line used by the networking device to connect to the network. As discussed above, the telephone 300 and the networking device 350 may be connected to the SSP over separate telephone lines. In the case where two lines are used to connect the telephone 300 and the networking device 350, the Internet DN and the voice DN will be distinct. However, in the case where the  
 15 telephone 300 and the networking device 350 are connected over the same telephone line (e.g., using a DSL modem 374), the Internet DN and the voice DN may be identical. The SCP 355 can store the data packet in association with a VIVR Session ID in a Session ID database 370. The SCP 355 can access the Session ID database 370 via TCP/IP data link 312 and the secure intranet 372. The presence of a Session ID in the Session ID Database  
 20 indicates that the networking device 350 is equipped to support a VIVR Session.

#### An Exemplary Method for Providing Visual and Audible Information

Figure 4 is a flow chart depicting a generalized method for initiating and terminating an exemplary VIVR session. A more detailed method is described in  
 25 connection with Figure 7. The method begins at step 400 and proceeds to step 402. At step 402, the user establishes an Internet connection with the VIVR provider. The method then proceeds to step 404 and the user establishes a telephone connection with the VIVR provider. Because the user has established both an audio-based connection (via telephone) and a visual-based connection (via Internet), a VIVR session can be

supported. The VIVR provider prompts the user by telephone to enable a VIVR Session at step **406**. That is, the VIVR provider invites the user to initiate a VIVR session. In an exemplary embodiment of the present invention, the VIVR provider can determine whether the VIVR Session can be supported by determining whether the user has an active Internet connection.

The method proceeds from step **406** to decision block **408**. At decision block **408**, a determination is made as to whether VIVR has been enabled. If the user has not enabled a VIVR session, the method proceeds from decision block **408** to step **420**. At step **420**, the VIVR provider prompts the user to choose between a telephony-based or a visual-based interaction. Because the user has chosen not to initiate a VIVR session (at decision block **408**), the provider allows the user to proceed with accessing the automated information delivery system by a conventional, telephony-based IVR session or by use of the provider's Internet website. The method proceeds from step **420** to decision block **418**. At decision block **418**, a determination is made as to whether the user has selected to initiate a conventional, telephony-based IVR session only. If the user has selected a telephony-only session, the method proceeds from decision block **418** to step **424**. At step **424**, the automated information is presented via telephone only. The method then proceeds to step **426** and ends.

Returning now to decision block **418**, if a determination is made that the user has selected an Internet-based session only, the method branches from decision block **418** to step **422**. At step **422**, the automated information is presented to the user via an Internet-based session only. The method then proceeds to step **426** and ends.

Returning now to decision block **408**, if a determination is made that the user has enabled a VIVR session, the method branches to step **410** and a VIVR session is initiated. The method then proceeds to step **412** and the VIVR provider prompts the user for operation parameters. These parameters may be made available to the user on a continuous basis throughout the duration of the VIVR session. The operation parameters may include terminating the telephony connection, terminating the Internet connection,

redirecting the telephony information to a networking device-based speaker and/or microphone and other operating parameter options.

The method proceeds from step **412** to decision block **414**. At decision block **414**, a determination is made as to whether the VIVR session has been terminated.

5 If, for example, the user terminates either the Internet connection or the telephonic connection, the VIVR session will be terminated, in that the simultaneous presentation of visual and audible information will be terminated.

If a determination is made at decision block **414** that the VIVR session has not been terminated, the method proceeds to step **416**. At step **416**, the automated information is presented simultaneously visually and telephonically. The method then loops back to step **412** and proceeds as described above until the VIVR session is terminated.

If, at decision block **414**, a determination is made that the VIVR session has been terminated, the method branches from decision block **414** to decision block **418**.  
15 At decision block **418**, a determination is made as to whether the user has selected a telephone-only session (conventional IVR session). The method branches from decision block **418** to either step **422** or step **424**, as described above.

## An Exemplary VIVR System Employing a Voice XML Gateway

Figure 5 is a block diagram of an exemplary embodiment of the present invention that employs a Voice XML (VXML) gateway 553. Voice Extensible Markup Language (VXML) is an XML derivative that is a communications standard directed to delivering Internet content and data that is accessible through voice-based devices (e.g., conventional telephone). One objective of the VXML standard is to provide speech-enabled applications over the Internet. Typically, VXML is implemented in applications involving speech recognition in which spoken commands are used to access information or complete transactions. Similarly, VXML can be used to deliver Internet content to a voice-based device in an audible format. For example, an IVR menu may be stored in

text-only format in an IVR server. That text can be processed by the VXML Gateway 553 and delivered to the telephone 500 as an audible message.

The VXML Gateway can convert the text-based data received from the VIVR Server 552 to audio-based content via known text-to-speech algorithms. Pre-  
5 stored audio files, such as ".wav" files may also be used. The VXML Gateway 553 may then play back the audio file over a connection with the telephone 500, established through the SSP 554. Those skilled in the art will appreciate that while the present invention is described as using the VXML communications standard, other communications standards could be used to implement alternative embodiments of the  
10 present invention.

The VXML Gateway **553** also can be used to interpret commands sent by a user, via the telephone **500**. The interpreted commands can be converted to an instruction that can be delivered to the VIVR Server **552**. In one embodiment of the present invention, the VXML Gateway **553** may employ a look-up table to correlate or  
15 translate received audible instructions with data-formatted instructions that are meaningful to the VIVR Server **552**. Thus, the VIVR Server **552** can use the VXML Gateway to deliver text-based information to a user in an audible format and to interpret audible instructions from the user. Among other advantages, this enables a simplification of the functionality of the VIVR Server **552**.

When a user of the telephone **500** wishes to begin an IVR session, the user can dial a conventional telephone number to contact the VIVR Server's host. If the user has an active Internet connection, the call can be connected to the VXML Gateway **553** by the conventional AIN components, including the SSP **554** and the SCP **555**. The SCP **555** can be used to route the call to the VXML Gateway **553**, in response to a trigger fired by the SSP. Accordingly, a conventional IVR (i.e., telephony only) session can be established between the telephone **500** and the VIVR Server **552**. The VXML Gateway **553** communicates with the VIVR Server **552** via TCP/IP communication links. The VXML Gateway **553**, thereby, enables the communication between the telephone **500** and the VIVR Server **552**. The VIVR Server **552** can prompt the user of the telephone

**500** to choose between continuing a telephony-only IVR session or establishing simultaneous visual and telephonic access to the information delivered by the VIVR Server.

The VIVR Server **552** utilizes the VXML Gateway **553** via a TCP/IP communication link. The VIVR Server **552** can deliver data to the VXML Gateway, which will then deliver an audible version of the data to the telephone **500**. Advantageously, the VIVR Server **552** can use the same data sent to the VXML Gateway **553** to generate audible messages to the telephone **500** to generate visually-formatted data for a networking device **550**. A more detailed description regarding this functionality is provided in connection with Figure 6.

A user may initiate a VIVR Session with the VIVR Server **552** by establishing an Internet-based (i.e., visual-based) session in addition to the telephony-based connection. The user can gain Internet-based access to the VIVR Server's host (not-shown) by accessing the user's Internet Service Provider (ISP) **558** in the conventional way and then logging into a website maintained by the VIVR Server host. The login procedure and/or a dial-up sequence may be automatically or manually generated by the networking device **550** to indicate that the user of the networking device intends to establish a VIVR session. The ISP **558** can store a VIVR Session ID in a Session ID database **570**. The VIVR Session ID indicates that the networking device **550** is online and able to establish and conduct a VIVR session.

Those skilled in the art will appreciate that various forms of the VIVR Session ID could be used to implement various embodiments of the present invention. In an exemplary embodiment, the VIVR Session ID includes the Internet directory number corresponding to the networking device **550**, the Internet protocol address (IP address) of the networking device, and the voice directory number associated with the networking device. The Internet directory number is the telephone number associated with the telephone line through which the networking device **550** has gained access to the ISP **558**. This number is known by the relevant AIN components and can be obtained from the SSP **554**. Likewise, the voice directory number is a telephone number that is

associated with the Internet directory number. In the case of a DSL connection, the Internet directory number and the voice directory number may be identical. Otherwise, the Internet directory number and the voice directory number are distinct, such as would be the case where a user is using separate lines for Internet access and conventional telephone access. The IP address is typically assigned to the networking device **550** by the ISP **558**.

When a user contacts the VIVR Server host via the telephone **550**, the user may select to establish a VIVR session (i.e., visual and telephonic access) when prompted. In the case where a user selects to establish a VIVR session, a VIVR Application **580** running on the SCP **555** can determine whether a VIVR Session ID exists for the user in the Session ID database **570**. The VIVR Application **580** makes this determination by first determining the voice directory number of the connected user. The voice directory number can then be compared to the Session ID database **570** to determine whether a Session ID containing the voice directory number exists. If such a Session ID exists, the VIVR application **580** knows that the networking device **550** associated with the telephone **500** is online and able to establish a VIVR session. The VIVR Application **580** can then cause the SCP **555** to route the telephone call to the VXML Gateway **553**. The VXML Gateway **553** may then prompt the user to choose whether to establish a VIVR session.

If a user elects to establish a VIVR session, the VXML Gateway **553** may retrieve the requested information from the VIVR Server **552** for delivery as audible information to the telephone **500**. The VXML Gateway **553** will instruct the VIVR Server **552** to deliver visual information directly to the networking device **550** in a format suitable for visual representation (e.g., HTML).

Figure 6 is a block diagram depicting the interaction between an exemplary VIVR Server **601** and an exemplary VXML translation unit **602** that may be part of a VXML Gateway. The VIVR Server **601** can maintain VXML data in a VXML data file **608**. The VIVR Server may also maintain VXML web content in a separate VXML web content file **610**. Those skilled in the art will appreciate that the VXML data

file **608** and the VXML web content file may be the same file. The VIVR Server **601** can transmit VXML data to the VXML translation unit **602**. The VXML translation unit **602** has a VXML to Speech sub-component **606** that translates the VXML data to an audible message. The audible message can then be delivered to the telephone **600**. The VXML translation unit **602** also can receive spoken message or audible messages from the telephone **600** and process these messages through a Speech to VXML sub-component **604**. Once translated to VXML, the message from the telephone **600** can be delivered to the VIVR Server **601**. Advantageously, the VXML web content can be delivered directly to a networking component **612** or can be delivered to the networking component via the VXML translation unit **602**. In either case, the VIVR Server can deliver the same content to the telephone **600** and to the networking device **612**.

Although the VXML data file **608** and the VXML web content file **610** are depicted as separate components in the VIVR Server **601**, those skilled in the art will appreciate that one of the advantages of XML data is that the same XML data can be used to generate an audible message and an HTML-formatted web page. Because VXML is a derivative of XML, VXML also can be implemented in such a way as to benefit from this advantage.

#### An Exemplary Method for Providing a VIVR Session

Figure 7 is a flow chart depicting an exemplary method for providing simultaneous visual and telephonic access to an exemplary Visual Interactive Voice Response (VIVR) system. The method of Figure 7 can be used to establish a conventional IVR session and/or a Visual IVR session. The method begins at step **700** and proceeds to step **702**. At step **702**, an AIN feature code is received from a dial string. The feature code may be embedded in a dialing string that is dialed by a networking device to connect to an ISP. Alternatively, the AIN feature code may be generated during a login procedure where, for example, a networking device logs into a website maintained by the VIVR Server host. The method proceeds from step **702** to **704**.



5

10

15

25

At decision block **716**, a determination is made as to whether a VIVR Session ID corresponding to the VIVR session request is found in a Session ID database.

As described above, the voice directory number associated with the VIVR session request may be known. This voice directory number may be used to correlate the VIVR session request with a VIVR Session ID in a Session ID database. If the VIVR Session ID corresponding to the VIVR session request is found in the Session ID database, the method branches from decision block 716 to step 730.

At step 730, a VIVR session is provided, wherein both telephonic and visual access to the VIVR Server are simultaneously provided. As described above, the telephonic-based information may be conveyed to the telephone via a VXML Gateway, while the visual information may be transmitted via a TCP/IP connection to a networking device. The method proceeds from step 730 to decision block 724, wherein a determination is made as to whether the session is terminated. As described above, such a termination may include the termination of the voice telephone connection, the termination of the Internet connection, or both. If no such session termination has occurred, the method will branch back to step 730 and the VIVR session will be provided until such termination occurs.

If, at decision block 724, a determination is made that the VIVR session is terminated, the method branches to step 722. At step 722, a termination notice is transmitted. This step may be performed by the SSP, whereby the SSP transmits a message (e.g., TCAP TerminationNotification Message) containing the user's Internet directory number to an SCP. The method proceeds from step 722 to step 726. At step 726 the IP address, voice directory number, and the Internet directory number are removed from storage. Typically, this step will be performed by the SCP in cooperation with the Session ID database. In any event, this information will be removed from the Session ID database, indicating that the identified networking device is no longer able to establish and/or maintain a VIVR session. The method proceeds from step 726 to step 728 and ends.

Returning now to decision block 716, if a determination is made that no VIVR Session ID exists in the Session ID database, the method branches from decision block 716 to step 718. At step 718, a conventional IVR session is provided. Notably, a

0984206-06201

VIVR session is not and cannot be provided, because the absence of a VIVR Session ID indicates that the networking device associated with the voice directory number is not capable of establishing and/or maintaining a VIVR session. In most cases, this means that the networking device is not connected to the Internet.

5           The method proceeds from step **718** to decision block **720**. At decision block **720**, a determination is made as to whether the IVR session is terminated. If the IVR session is not terminated, the method branches back to step **718** and the IVR session is continued until such a termination occurs. If, at decision block **720**, a determination is made that the session has been terminated, the method branches to step **722**. At step **722**,  
10 a termination notice is transmitted as described above. The method then proceeds to step **726**, wherein the IP address, the voice directory number, and the Internet directory number are removed from the Session ID database. The method then proceeds to step **728** and ends.

In an exemplary embodiment of the present invention, a user can initiate a  
15 VIVR Session by calling the telephone number of a VIVR host. An AIN trigger (e.g., in an SSP associated with the VIVR host) may be configured to fire any time the VIVR host's telephone number is dialed. In response to the firing of the trigger, a query (e.g., TCAP InfoAnalyzed) is sent to an SCP. The query contains the user's directory number, which is a telephone number associated with the telephone on which the user is calling.  
20 The SCP returns an AIN responsive message to the SSP. The message may be an Analyze Route message with a Send Notification to the SSP. The trigger may cause the SCP to determine whether the user has an active Internet connection that can support a VIVR Session. These are well known AIN messages and operate to indicate to the SSP that the call should be routed to a VXML Gateway and also operate to instruct the SSP to  
25 notify the SCP when the call ends.

The SCP recognizes that the TCP/IP message corresponds to an active Internet connection, because the Internet directory number is in the SCP's Session ID database. The Internet directory number is in the SCP database, because the SCP stored the Internet directory number, in response to the firing of the AIN feature code trigger

103290-90246850

when the user established the active Internet connection. The Internet directory number, the IP address, and the voice directory number are collectively referred to as the VIVR Session ID. The SCP forwards the Session ID to a Session ID database, which stores the VIVR Session ID, indicating that a VIVR session is available to the user. When the Internet connection is terminated, the SSP sends a termination notification message (e.g., TCAP TerminationNotification) to the SCP containing the user's Internet directory number. When the SCP receives the termination notification message, the SCP transmits a request to the Session ID database to remove the VIVR Session ID.

When it is established that a VIVR Session ID is present in the Session ID database, the VIVR Server may prompt the user over a telephonic connection to select between an IVR session and a VIVR session. If the user desires to establish a VIVR session, the SCP will route the telephone call to a VXML Gateway. The SCP may set a flag indicating that the user has requested a VIVR session. For example, the SCP may use the well-known RedirectingPartyID field in an AIN message. This field may be set to all "ones" to indicate that the user has requested a VIVR session. If the user requests a telephony-only session (IVR session) the SCP will still route the call to the VXML Gateway, but will set the flag to indicate that the user has not requested a VIVR session. For example, the RedirectingPartyID field may be set to null.

If a VIVR session is not requested, the requested content may be delivered to the user's telephone via the VXML Gateway and a conventional IVR session may be conducted. The VXML Gateway can deliver content to the telephone in the form of audible messages, such as playing back ".wav" files. The user may issue speech or DTMF key code instructions to the VXML Gateway, which will forward the instructions to the VIVR Server.

If the user requests a VIVR session, the VIVR Server can deliver the XML content to the VXML Gateway and can simultaneously deliver corresponding HTML-formatted web pages to the user's networking device at the user's IP address identified in the VIVR Session ID. The XML content and the HTML content can be synchronized so that the delivery of the HTML content to the networking device occurs at or near the

05594206 062301

5

10

15

25

Although the present invention has been described in connection with various exemplary embodiments, those of ordinary skill in the art will understand that many modifications can be made thereto within the scope of the claims that follow. Accordingly, it is not intended that the scope of the invention in any way be limited by

	1980	1981	1982	1983	1984	1985	1986	1987	1988	1989	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100	2101	2102	2103	2104	2105	2106	2107	2108	2109	2110	2111	2112	2113	2114	2115	2116	2117	2118	2119	2120	2121	2122	2123	2124	2125	2126	2127	2128	2129	2130	2131	2132	2133	2134	2135	2136	2137	2138	2139	2140	2141	2142	2143	2144	2145	2146	2147	2148	2149	2150	2151	2152	2153	2154	2155	2156	2157	2158	2159	2160	2161	2162	2163	2164	2165	2166	2167	2168	2169	2170	2171	2172	2173	2174	2175	2176	2177	2178	2179	2180	2181	2182	2183	2184	2185	2186	2187	2188	2189	2190	2191	2192	2193	2194	2195	2196	2197	2198	2199	2200	2201	2202	2203	2204	2205	2206	2207	2208	2209	2210	2211	2212	2213	2214	2215	2216	2217	2218	2219	2220	2221	2222	2223	2224	2225	2226	2227	2228	2229	2230	2231	2232	2233	2234	2235	2236	2237	2238	2239	2240	2241	2242	2243	2244	2245	2246	2247	2248	2249	2250	2251	2252	2253	2254	2255	2256	2257	2258	2259	2260	2261	2262	2263	2264	2265	2266	2267	2268	2269	2270	2271	2272	2273	2274	2275	2276	2277	2278	2279	2280	2281	2282	2283	2284	2285	2286	2287	2288	2289	2290	2291	2292	2293	2294	2295	2296	2297	2298	2299	2300	2301	2302	2303	2304	2305	2306	2307	2308	2309	2310	2311	2312	2313	2314	2315	2316	2317	2318	2319	2320	2321	2322	2323	2324	2325	2326	2327	2328	2329	2330	2331	2332	2333	2334	2335	2336	2337	2338	2339	2340	2341	2342	2343	2344	2345	2346	2347	2348	2349	2350	2351	2352	2353	2354	2355	2356	2357	2358	2359	2360	2361	2362	2363	2364	2365	2366	2367	2368	2369	2370	2371	2372	2373	2374	2375	2376	2377	2378	2379	2380	2381	2382	2383	2384	2385	2386	2387	2388	2389	2390	2391	2392	2393	2394	2395	2396	2397	2398	2399	2400	2401	2402	2403	2404	2405	2406	2407	2408	2409	2410	2411	2412	2413	2414	2415	2416	2417	2418	2419	2420	2421	2422	2423	2424	2425	2426	2427	2428	2429	2430	2431	2432	2
--	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	---